WTCI-317-P

0011986

USM

UNITED STATES MINERAL PRODUCTS COMPANY

SINCE 1875

STANHOPE, NEW JERSEY 07874

Tel. 347-1200 Area Code 201
Cable, CAFCOINSUL, New York

March 23, 1970

Mario & DiBono Plastering Co., Inc.
370 Northern Blvd.
Great Neck, New York

EXHIBIT
ID. P-46
JUL 08 1991
JENNIFER M. BONFILIO, C.S.R.

Attention: Mr. Louis DiBono

Dear Mr. DiBono:

Reference is made to your request regarding the physical properties of U.S. Mineral Products Mark II coating.

Mark II coating is a fibrated hydraulic product which when applied flows together forming a tight durable cementitious finish.

Physical Properties

A. Air erosion resistance; Mark II has a durable hard finish and an air erosion resistance meeting the General Services Administration (G.S.A.) specification of resisting air velocity of not less than 800 F.P.M. and a loss of not more than zero point zero two five grams per square foot for a 24 hour period.

B. Hardness; The hardness of Mark II is dependent on its thickness and applied surface; but is considerable harder than the cafco blaze shield Type D.

C. Bonding; Mark II will bond to cafco blaze shield Type D and will not delaminate. The Bond between Mark II and Type D is stronger than the cafco blaze shield Type D bonds within itself.

D. Fire Resistance; The inorganic formulation of Mark II coating will not support combustion and will not affect the fireproofing quality of the cafco Type D to which it is applied.

We anticipate that the information contained herein is sufficient. If you require additional details please let us know.

Sincerely yours,

U.S. MINERAL PRODUCTS COMPANY

EXHIBIT
Verhalen-15
9-10-96

Frank M. Stumpf,
Vice President of Research

MINERAL FIBER AND FRAMED PLASTIC PRODUCTS FOR HIGH AND LOW TEMPERATURE

CAFCO SPRAYED FIBER PRODUCTS FOR FIREPROOFING, INSULATION OF BUILDINGS AND EQUIPMENT, AND ACOUSTICAL TREATMENT